

Portas necessárias para o funcionamento do MS-Lync, quando existe bloqueio à rede externa pelo Órgão que tenciona a assistir à palestra por acesso remoto.

Component	Port	Protocol	Notes
Clients	67/68	DHCP	Used by Lync Server 2010 to find the Registrar FQDN (that is, if DNS SRV fails and manual settings are not configured).
Clients	443	TCP (TLS)	Used for client-to-server SIP traffic for external user access.
Clients	443	TCP (PSOM/TLS)	Used for external user access to web conferencing sessions.
Clients	443	TCP (STUN/MSTURN)	Used for external user access to A/V sessions and media (TCP)
Clients	3478	UDP (STUN/MSTURN)	Used for external user access to A/V sessions and media (TCP)
Clients	5061	TCP (MTLS)	Used for client-to-server SIP traffic for external user access.
Clients	6891-6901	TCP	Used for file transfer between Lync 2010 clients and previous clients (clients of Microsoft Office Communications Server 2007 R2, Microsoft Office Communications Server 2007, and Live Communications Server 2005).
Clients	1024-65535 *	TCP/UDP	Audio port range (minimum of 20 ports required)
Clients	1024-65535 *	TCP/UDP	Video port range (minimum of 20 ports required).
Clients	1024-65535 *	TCP	Peer-to-peer file transfer (for conferencing file transfer, clients use PSOM).
Clients	1024-65535 *	TCP	Application sharing.

TCP/443	UDP/3478
---------	----------